



# DesignLights Consortium

QUALIFIED LUMINAIRES REFERENCE



FOCAL POINT®

## RECESSED

Fixture	Luminaire Series	Nominal Size	Shielding	Lumen Output	Color Temperature	Circuit	Voltage	Driver	Mounting	Options	Finish				
AERION LED	FARL	14	AC	2500L	30K	1C	120	L11	G1	AR, CP, EM,	WH				
			RA*	3000L	35K		277	LD1	G2	FNY, FW	WHA				
			SA*	3500L	40K		UNV	G3							
				4000L	*RA & SA not DLC with 4000L										
		22	AC	2000L	30K	1C	120	L11	G1	AR, CP, EM,	WH				
				2500LH	35K		277	LD1	G2	FNY, FW	WHA				
				3000LH	40K		UNV	G3							
				3500LH											
		24	AC	4000L	30K	1C	120	L11	G1	AR, CP, EM,	WH				
			RA*	4000LH	35K		277	LD1	G2	FNY, FW	WHA				
			SA*	4500L	40K		UNV	G3							
				4500LH											
			5000L												
			5000LH												
			5500L												
	5500LH														
	6000LH	*RA & SA not DLC with 5000L or 5500L													
AMICA 2	FAM2	22	ACR	2500L†	30K	1C	UNV	LD1	G	AR	WH				
				2500LH	35K				F	CP					
				3000L†	40K				SM	EM					
				3000LH					C24	FNY1					
				3500L†					C48	FNY2					
				3500LH					C96	FW					
				4000L†											
				4000LH	†Indicates DLC Standard qualified products										
			24	ACR	4000L				30K	1C	UNV	LD1	G	AR	WH
					4000LH				35K				F	CP	
					4500L				40K				SM	EM	
					4500LH								C24	FNY1	
		5000L			C48	FNY2									
		5000LH			C96	FW									
		5500L													
	5500LH														
	6000L														
	6000LH														
AMICA LED	FAML	22	ACR	2000L	30K	1C	120	L11	G1	AR, CP, EM,	WH				
				2500LH	35K		277	LD1	G2	FNY, FW	WHA				
				3000LH	40K		UNV	G3							
				3500LH											
		24	ACR	4000L	30K	1C	120	L11	G1	AR, CP, EM,	WH				
				4000LH	35K		277	LD1	G2	FNY, FW	WHA				
				4500L	40K		UNV	G3							
				4500LH											
				5000L											
				5000LH											
				5500L											
				5500LH											
		6000LH													

Amica 2 versions listed are DLC Premium unless otherwise indicated. Visit [designlights.org/QPL](http://designlights.org/QPL) for model specifics.



# DesignLights Consortium

QUALIFIED LUMINAIRES REFERENCE



FOCAL POINT®

## RECESSED continued

Fixture	Luminaire Series	Nominal Size	Shielding	Lumen Output	Color Temperature	Circuit	Voltage	Driver	Mounting	Options	Finish		
EQUATION 2	FEQ2	14	AC	2000L	35K	1C	UNV	LD1	C24	AR	WH		
			MG	2500L	40K			L11	C48	CP			
										C96	EM		
										F	FNY1		
										G	FNY2		
										ST	FW		
										SM			
				22	AC	2000LH	35K	1C	UNV	LD1	C24	AR	WH
			MG		2500LH	40K	L11			C48	CP		
						3000LH					C96	EM	
						3500LH					F	FNY1	
											G	FNY2	
									ST	FW			
									SM				
		24	AC	4000LH	35K	1C	UNV	LD1	C24	AR	WH		
	MG		4500LH	40K	L11			C48	CP				
				5000LH					C96	EM			
				5500LH					F	FNY1			
				6000LH					G	FNY2			
				6500LH					ST	FW			
				7000LH					SM				
FACETTA	FCT	22	FL	2000L	27K	1C	UNV	L11	F		WH		
				2500L	30K			LD1	G				
				3000L	35K				ST	CP, EM, FNY1,			
				3500L	40K					FNY2, FW			
				4000L									
VEER LED	FVRL	24	ACF	4000L	30K	1C	120	L11	F	AR, CP, EM,	WH		
			ACG	4000LH	35K			LD1	G	FNY, FW			
			ACR	4500LH	40K				ST				
				5000LH					SM				
				5500LH									
				6000LH									
ZEPHYR	FZR	14	FL	2000L	27K	1C	UNV	L11	F	CP, EM, FNY1,	WH		
					30K			LD1	G	FNY2, FW			
					35K				ST				
					40K								
			22	FL	2000L	27K	1C	UNV	L11	F	CP, EM, FNY1,	WH	
					2500L	30K			LD1	G	FNY2, FW		
					3000L	35K				ST			
					3500L	40K							
					4000L								



# DesignLights Consortium

QUALIFIED LUMINAIRES REFERENCE



FOCAL POINT®

## RECESSED LINEAR

Fixture	Luminaire Series	Shielding	Nominal Output	Color Temperature	Circuit	Voltage	Driver	Ceiling Configuration	Factory Options	Finish	Length
SEEM 4 LED ASYMMETRIC ANGLED LENS	FSM4AL	FL	375LF*	30K	1C	UNV	L11	G1, T1, G2, T2, G3, T3, G5, T5, T6, TF, TFW, XF1, XF2, XFF, XFN, XFW, CXF1, CXF2, CXFF, CXFN, CXFW	CP, EC, EM, FNY1, FNY2, FW	WH	Individual units 2-8' and runs comprised of 2-8' units
			625LF	35K			LD1				
			875LF	40K							
SEEM 4-LP	FSM4LP	FL	375LF*	30K	1C	UNV	LD1	G1, T1, G2, T2, G3, G4, T4, G5, T5, T6	CP, EC, EM, FNY1, FNY2, FW	WH	Individual units 2' and 4' - 8' lengths and runs comprised of 4' - 8' units
			625LF	35K			L11				
			875LF	40K							
			1000LF								

\*375LF 4' length minimum

\*375LF 4' - 8' only.

## LINEAR

Fixture	Luminaire Series	Shielding	Nominal Output	Color Temperature	Circuit	Voltage	Driver	Mounting	Factory Options	Finish	Length	
TWELVE LED	FTWLS	AC	750LF	30K*	1C	UNV	LD1	J12	DC, EC, EM	TS	4'	
			MG	875LF				35K		J24	WH	8'
				1000LF				40K		J48		12' (8' + 4')
				1125LF						J96		16' (8' + 8')
				1250LF						S__		20' (8' + 4' + 8') 24' (8' + 8' + 8')

\*30K not DLC with 875LF, 1000LF or 1250LF

Fixture	Luminaire Series	Shielding	Nominal Output	Color Temperature	Circuit	Voltage	Driver	Mounting	Suspension & Power Feed	Factory Options	Finish	Length	Run Configurations
NERA	FNRS	FL60	500LF	30K	1C	UNV	LD1	G, HS, OC	CLV24	CCS, CP,	PS	4'	C4
		FL70	625LF	35K					CLV48	EC, EM	WH	5'	C5
			750LF*	40K					CLV60			6'	C6
			875LF*						CLV96			8'	C8
			1000LF										M

\*Consult cutsheet run guide for standard configurations

\*750LF and 875LF not DLC with 4', 5' or 6' lengths

OBSCURA	FOSS	FL80	500LF	30K	1C	UNV	LD1	G, HS, OC	CLV24	CCS, CP,	PS	4**	
			625LF	35K					CLV48	EC, EM	PSM	5**	
			750LF	40K					CLV60		WH	6**	
			875LF						CLV96		WHM	7'	
			1000LF									8'	
												9'	
												10'	
						11'							
						12'							

\*\*4' 500LF DLC with 40K color temperature only. 5' & 6' 500LF DLC with 35K & 40K color temperatures only.