




Avenue® A

FLUORESCENT RECESSED WALL MOUNT




recessed companion



linear companion

DIMENSIONAL DATA



FEATURES

ADA compliant, high performance T5/T5HO recessed wall mounted fluorescent.


Asymmetric indirect distribution in a 2" aperture.

Designed for new construction applications.

Luminaire only protrudes ½" from the wall.

Great solution for corridors and small offices.

PERFORMANCE



PRODUCT OVERVIEW

Lumen Output: 548-2842lm
 Wattage: 16-91W
 Lamping: T5, T5HO


1-Lamp T5HO
 58% Efficient
 1726 cd @ 135°

Visit focalpointlights.com for complete photometric data.

fixture:

project:

MOUNTING INFORMATION



SPECIFICATIONS

Construction

One-piece 20 Ga. steel housing. 20 Ga. steel rough-in box supports fixture in wall (designed for new construction) and must be installed prior to drywall installation. 20 Ga. steel beveled flange, .5" in width. 2' unit weight: 4 lbs., 3' unit weight: 5 lbs., 4' unit weight: 7 lbs.

Optic

Upper reflector fabricated of .020" aluminum painted High Reflectance White powder coat. Bottom reflector fabricated of low iridescent .020" specular aluminum. 24 Ga. perforated steel diffuser finished in Matte Black.

Electrical

Luminaires are individually wired for specified circuits. Thru-wiring not available. Electronic ballasts are thermally protected and have a Class "P" rating. Optional dimming ballasts available. Consult factory for dimming specifications and availability.

Labels

UL and cUL listed.

Finish

Polyester powder coat applied over a 5-stage pre-treatment. Housing and all steel components are finished in Matte Satin White. Perforated diffuser always finished in Matte Black.

ORDERING

Luminaire Series		FAVAW
Avenue A		FAVAW
Shielding		
No Shielding, Open Optic		NS
Clear Lens		CL
Lamping		
One Lamp T5		1T5
One Lamp T5HO		1T5HO
Circuits		1C
Single Circuit		1C
Voltage		
120 Volt		120
277 Volt		277
347 Volt		347
<small>(Consult factory for dimming options)</small>		
120/277 UNV		UNV
<small>(Not available with 1-lamp T5HO dimming or EM)</small>		
Ballast		
Electronic Program Start <10% THD		S
0-10V		D7
Lutron 1% 3-wire		DH
Lutron 1% H-Series		DK
Mounting		RW
Recessed Wall Mount		RW
Factory Options		
Emergency Battery Pack*		EM
<small>(3' & 4' Luminaires Only)</small>		
HLR/GLR Fuse		FU
Include 3000K Lamp*		L830
Include 3500K Lamp*		L835
Include 4100K Lamp*		L841
Finish		WH
Matte White Housing		WH
<small>(Perforated diffuser always painted black)</small>		
Luminaire Length		
2' Nominal Housing		2'
<small>(Electronic Program Start only)</small>		
3' Nominal Housing		3'
4' Nominal Housing		4'
<small>(Row mount not recommended)</small>		

Avenue® A


FLUORESCENT - OPEN OPTIC

FAVAW-NS-1T5HO-1C-120-S-RW-WH-4'

Filename: FAVAWNS1T5H.IES
Test #: 12420.0

Lumens: 2879lm
Efficiency: 58%

CANDLEPOWER DISTRIBUTION



Vertical Angle	Horizontal Angle					Zonal Lumens
	0°	22.5°	45°	67.5°	90°	
0°	5	5	5	5	5	5
5°	5	5	5	5	5	1
15°	8	8	8	8	5	2
25°	7	7	4	1	1	1
35°	14	11	7	0	0	2
45°	18	15	8	0	0	3
55°	60	46	17	2	0	11
65°	131	108	53	4	0	28
75°	224	198	125	26	0	59
85°	331	299	212	75	0	102
90°	417	381	284	120	0	
95°	575	534	422	232	10	212
105°	984	936	806	504	34	383
115°	1295	1218	1035	698	75	479
125°	1502	1431	1242	756	125	493
135°	1726	1651	1408	728	176	464
145°	1580	1490	1124	597	221	330
155°	1260	1145	874	503	251	193
165°	811	747	601	420	287	92
175°	420	401	365	316	287	26
180°	270	270	270	270	270	

LUMEN SUMMARY

Zone	Lumens	% Lamp	% Fixture
0-30°	1073	21.5	37.3
0-40°	1567	31.3	54.4
0-60°	2360	47.2	82.0
0-90°	2671	53.4	92.8
Total Luminaire 0-180°	2879	57.6	100.0

Go to www.focalpointlights.com for additional photometric data.