



Energy Star[®]

QUALIFIED DOWNLIGHTS



FOCAL POINT[®]

ID+ 3.5"

Fixture	Housing Options								Trim Options										
	Housing Series	Trim Type	Color Options	Lumen Output	Voltage	Driver	Housing Type	Factory Options	Aperture	Trim Type	Lumen Output	Color Temp	Optic	Distribution	Reflector Color	Optional Flange Finish			
ID+ 3.5" DOWNLIGHT	FLC3D	RO RT	SW HC	700L	UNV	LD1	IC	BH	LC3	RO	700L	27K	DNT	NFL	CD	BP			
				900L							120	900L					30K	FL1	WD
				1100L							277	1100L					35K	FL2	WH
				1300L								1300L					40K	WFL	BK
				1500L								1500L					927K	VWFL	
				1700L								1700L					930K		
				1900L								1900L					935K		
				2100L								2100L					940K		
																	H27K		
																	H30K		
			H35K																
			H40K																
ID+ 3.5" X 3.5" DOWNLIGHT	FLC33D	SDO SDT	SW HC	700L	UNV	LD1	IC	BH	LC33	SDO	700L	27K	DNT	NFL	CD	BP			
				900L							120	900L					30K	FL1	WD
				1100L							277	1100L					35K	FL2	WH
				1300L								1300L					40K	WFL	BK
				1500L								1500L					927K	VWFL	
				1700L								1700L					930K		
				1900L								1900L					935K		
				2100L								2100L					940K		
																	H27K		
																	H30K		
			H35K																
			H40K																

Fixture	Housing Options								Trim Options									
	Housing Series	Trim Type	Color Options	Lumen Output	Voltage	Driver	Housing Type	Factory Options	Aperture	Trim Type	Lumen Output	Color Temp	Optic	Reflector Color	Optional Flange Finish			
ID+ 3.5" WALL WASH	FLC3W	RO RT	SW HC	700L	UNV	LD1	IC	BH	LC3	RO	700L	27K	WWT	CD	BP			
				900L							120	900L				30K	WWS	WH
				1100L							277	1100L				35K	BK	
				1300L								1300L				40K		
				1500L								1500L				927K		
				1700L								1700L				930K		
				1900L								1900L				935K		
				2100L								2100L				940K		
																H27K		
																H30K		
			H35K															
			H40K															
ID+ 3.5" X 3.5" WALL WASH	FLC33W	SDO SDT	SW HC	700L	UNV	LD1	IC	BH	LC33	SDO	700L	27K	WWT	CD	BP			
				900L							120	900L				30K	WWS	WD
				1100L							277	1100L				35K	WH	
				1300L								1300L				40K	BK	
				1500L								1500L				927K		
																930K		
																935K		
																940K		
																H27K		
																H30K		
			H35K															
			H40K															



Energy Star[®]

QUALIFIED DOWNLIGHTS



FOCAL POINT[®]

ID+ 4.5"

Fixture	Housing Options							Trim Options							
	Housing Series	Trim Type	Output	Voltage	Driver	Housing Type	Factory Options	Aperture	Trim Type	Output	Color Temp.	Optic	Distribution	Color	Flange Finish
ID+ 4.5" DOWNLIGHT	FLC4D	RT RO	1000L	UNV	L11	T	BH	LC4 LC4AT	RO RT	1000L	27K	DN	SP	CD	NP
			1500L	120	LD1	IC	CP			1500L	30K		NFL	WH	BP
			2000L	277						2000L	35K		FL1	WD*	WP
			2500L							2500L	40K		FL2	BK	
			3000L							3000L	927K		WFL		
											930K				
							935K								
							940K								

*80CRI only

ID+ 4.5" X 4.5" DOWNLIGHT	FLC44D	SO ST	1000L	UNV	L11	T	BH	LC44 LC4AT	SDO SDT	1000L	27K	DN	SP	CD	NP
			1500L	120	LD1	IC	CP			1500L	30K		NFL	WH	WH
			2000L	277						2000L	35K		FL1	WD*	BK
			2500L							2500L	40K		FL2	BK	
			3000L							3000L	927K		WFL		
											930K				
							935K								
							940K								

*80CRI only

Fixture	Housing Options							Trim Options								
	Housing Series	Trim Type	Color Options	Lumen Output	Voltage	Driver	Housing Type	Factory Options	Aperture	Trim Type	Lumen Output	Color Temp.	Optic	Reflector Color	Optional Flange Finish	
ID+ 4.5" WALL WASH	FLC4W	RO RT	SW	1000L	UNV	L11	T	BH	LC4 LC4AT	RO RT	1000L	27K	WW	CD	NP	
				1500L	120	LD1	IC	CP			1500L	30K		WD	BP	
				2000L	277						2000L	35K		WH	WP	
				2500L							2500L	40K		BK		
				3000L								927K				
												930K				
							935K									
							940K									

ID+ 4.5" X 4.5" WALL WASH	FLC44W	SO ST	SW	1000L	UNV	L11	T	BH	LC44 LC44AT	SDO SDT	1000L	27K	WW	CD	NP	
				1500L	120	LD1	IC	CP			1500L	30K		WD	BP	
				2000L	277						2000L	35K		WH	WP	
												40K		BK		
												927K				
												930K				
							935K									
							940K									



Energy Star[®]

DIMMING COMPATIBILITY



FOCAL POINT[®]

All Energy Star-certified fixtures offer continuous dimming capability from either 100%-10% (LD1 option) or 100%-1% (L11 option). For more information on dimmer compatibility, please consult the driver manufacturers documentation.

Fixture	Housing Series	Lumen Range	Driver	Manufacturer Reference
ID+ 3.5"	FLC3D	All	L11 LD1	Advance Xitanium 25W (XI025C100V036DSM1, XI025C100V036DSM5) Datasheet
	FLC3W			
ID+ 3.5" X 3.5"	FLC33D	All	L11 LD1	Advance Xitanium 25W (XI025C100V036DSM1, XI025C100V036DSM5) Datasheet
	FLC33W			
ID+ 4.5"	FLC4D	1000L-3000L	L11 LD1	Advance Xitanium 25W (XI025C100V036DSM1, XI025C100V036DSM5) Datasheet
				Advance Xitanium 50W (XI050C140V054DSM1, XI050C140V054DSM5) Datasheet
	FLC4W	1000L-3000L	L11 LD1	Advance Xitanium 25W (XI025C100V036DSM1, XI025C100V036DSM5) Datasheet
				Advance Xitanium 50W (XI050C140V054DSM1, XI050C140V054DSM5) Datasheet
ID+ 4.5" X 4.5"	FLC44D	1000L-3000L	L11 LD1	Advance Xitanium 25W (XI025C100V036DSM1, XI025C100V036DSM5) Datasheet
				Advance Xitanium 50W (XI050C140V054DSM1, XI050C140V054DSM5) Datasheet
	FLC44W	1000L-2000L	L11 LD1	Advance Xitanium 25W (XI025C100V036DSM1, XI025C100V036DSM5) Datasheet
				Advance Xitanium 50W (XI050C140V054DSM1, XI050C140V054DSM5) Datasheet